

# SNAPGRID®

## SnapGRID® LX2 Interlocking Sport Tiles

Lay, Click, Repeat.

Create a DIY Sport Court in a Snap!

**MULTI-PURPOSE**

**XSPANBAND  
INTERLOCK SYSTEM**

**SELF-DRAINING**

*The SnapGRID® LX2 sport tile system is durable, portable, and outperforms asphalt and rubber court options in any application with exposure to accumulated moisture. LX2 tiles create a self-draining surface, while the new GatorSKIN finish provides extra grip and safety.*

*Easily configured to suit your specific needs, SnapGRID® LX2 anti-bacterial & anti-microbial drainage tiles are easy to work with, easy to clean, and ultra-durable; the perfect long-lasting alternative for any multi-purpose sport court or wet area requiring drainage.*



📍 2007 - 4 Highland Park Green NE  
Airdrie, AB T4A 0X3

☎ 587.775.8838  
888.363.6289

✉ sales@perfectsurfaces.ca

🌐 www.perfectsurfaces.com



**FOR IMPROVED BALL BOUNCE CONSISTENCY, LX2 BOASTS A MORE ROBUST SUPPORT SYSTEM THAN ORIGINAL LX TILES— AND NOW ALSO FEATURES BUILT-IN FASTENERS TO EASILY SECURE THE COURT TO ANY SUBFLOOR; PAIR THIS WITH ANTI-SLIP GATORSKIN FOR THE ULTIMATE SPORT COURT**

## STANDARD TILE DIMENSIONS

SIZE	THICKNESS
30CM x 30CM (12"x12")	12MM (1/2")

## SNAPGRID<sup>®</sup> LX2 SPECIFICATIONS

MATERIAL	POLYPROPYLENE (PP)
HIGH TEMP TOLERANCE	+80°C
LOW TEMP TOLERANCE	-50°C
REBOUND RATE	93%
SHOCK ABSORPTION	32%
COEFFICIENT OF FRICTION	0.62
VERTICAL DEFORMATION	0.49MM
TENSILE STRENGTH	0.9MPA
<b>RESISTANCE:</b>	
ANTI-SLIP (DRY TEST)	98.8BPN
ANTI-SLIP (WET TEST)	56.2BPN
ACID (30% SULFURIC ACID SOAK FOR 48 HOURS)	NO SIGNIFICANT CHANGE
ALKALI (20% SODIUM BICARBONATE SOAK FOR 48 HOURS)	NO SIGNIFICANT CHANGE



\* actual colours may vary slightly